

FLYER XL with Electrical Opening Legs PRODUCT SHEET



Description :

- Frame made in aluminium
- Laser cutting and bending sheet metal, tubes and profiles
- Epoxy baked painting
- Ball bearing castors
- Total weight : 55 kg
- Weight capacity : 300 kg
- Lifespan : 8 years (except electrical parts)

- Medical products (93/42 EEC amended by 2007/47/EEC)
- Electromagnetic compatibility (2004/108/EC)
- Applicable standards :
 - BS EN 60601-1 : 2007
 - BS EN 60601-1-2 : 2007
 - BS EN ISO 10535 : 2007
- DC motor low voltage 24V
- 24V / 120VA power
- Lifting Actuator maximum strength : 10 000 N
- Lifting Stroke : 29 cm
- Electronic protection when overloaded
- Protection class : II
- Protection type : IPX 4
- Stop limit switch
- Box in ABS
- Handcontrol with spiral cable, low voltage 24V
- Protection against overloading through thermo-switch

Motorization Technicals Characteristics :

- Removable battery pack
- Digital display of the autonomy
- Power cord
- Emergency stop button
- Remote control 4 functions protection class IPX4
- Electrical security lowering system
- Wall charger (in option)

Dimensionals Characteristics :

- A. Total length: 125 cm
- B. Minimum lifting height: 55 cm
- C. Maximum lifting height: 182 cm
- D. Total height: 125 cm
- E. Frame height: 11 cm
- F. Minimum base width: 73 cm
- G. Maximum base width: 105 cm
- H. Turning diameter: 143 cm

