

PRODUCT SHEET NAUSIFLOW 2 PUMP



Specifications:

- Very high prevention
- Alternating modes
- Mechanical pressure management
- 130 kg weight capacity
- Class 1 medical device
- Environmental conditions of use and storage:
 - Temperature: 10°C - 35°C
 - Humidity: 20% - 80%
- Electrical Classification:
 - Class II Type B, double insulation with or without ground wire.
 - IPX0, do not immerse the pump in a liquid, do not spray liquid directly on the pump.
 - This pump is not protected AP / APG (AP = flammable anesthetics in the air), (APG = flammable anesthetics with oxygen or nitrous oxide).
- Standards: EN 60601-1, EN 60601-1-2, EN 61000-3-2, EN 61000-3-3, UL-2601-1
- Electromagnetic compatibility: EN 60601-1-2: 1993
- Consumption: in normal use, max 12 W
- Power Cable: H05VV-F3x0.75mm²
- This product complies with the requirements for the safety and health of the Directive 93/42/EC concerning medical devices and the basic requirements of Directive 86/336/EC on electromagnetic compatibility.



Functions:

- Comfort setting: can manually adjust the pressure to optimize patient comfort.
- On / Off button: turns the compressor on and off

Key features :

Standard pressure setting
Self management of seating positions (less than 2 hours)
Management of seating positions (over 2 hours)
Alternating function
Visual and audible alarm: low pressure
Required pressure indicator